## FASTCAP L.L.C.

### \_\_\_\_\_

## **MATERIAL SAFETY DATA SHEET**

# **FastCap Screw Cover Caps**

**Product Identification:** Screw Cover Caps Manufactured from PVC sheet with Acrylic

PSA Adhesive.

Company Identification: FastCap L.L.C.

3725 Irongate Rd. #105 Bellingham, WA 98226

Chemical characteristics: PVC material - Semi hard PVC Barium/Cadium free stabilized.

Polystyrene material - General Purpose Polystyrene.

Adhesive - Based on CFR Title 29-1910.1200(5) (iv) (c), such products are considered exempt from notice requirements since

they do not release or otherwise result in exposure to a hazardous chemical under normal conditions of use.

Physical state: Solid

\_\_\_\_\_

## Safety Measures

1. Solubility in water (20 degrees C): Not soluble

- 2. Ignition temperature: Not applicable
- 3. Spontaneous combustion: Not applicable
- 4. Explosion limits: Not applicable
- 5. Thermal decomposition: When burnt under continuous flame generates CO and HCL
- 6. Dangerous Reactions: Not applicable
- 7. Other indications: Product only burns under permanent flame. It's self extinguishable

\_\_\_\_\_

#### **Dangerous Classification**

This is not a dangerous product.

#### \_Transport

No special requirements.

#### Storage and handling

Special measures not required.

\_\_\_\_\_

#### Safety technical measures

- 1. Personal safety: No special safety measures required
- 2. Residue elimination: Storage in adequate places(e.g. Municipal waste disposal areas)
- 3. Accident or Fire: Products to extinguish fires: Water and CO2 foam. In case of fires, use of gas mask adequate for CO and HCL.
- 4. Safety recommendations: Protection/Breathing: Not applicable

Protection/eyesight: Not applicable

Protection/hands: Not applicable
Ingestion: not applicable
5. Toxicology: No danger when normally used
6. Ecology: Residues should be dumped in Municipal waste disposal areas and recycled

Date: May 23, 2019